BO Motor Oil BV

 Rootven 10
 Tel.: (+31)497 - 38 48 47

 5531 MB Bladel
 Fax: (+31)497 - 38 40 55

 The Netherlands
 E-mail: info@bomotoroil.com

KVK nr. 61804312 BTW nr. NL 854495538 B01 Rabobank 10.75.97.055 IBAN nr. NL57 RABO 0107 5970 55 BIC-code: RABONL2U

#### **TECHNICAL DATASHEET**

UBRICANT.

# ATF LL LIFE PROTECT 8

Full Synthetic all-round low viscosity Automatic Transmission oil

**GOATF LL Life Protect 8** is a fully synthetic automatic transmission oil, which has been especially developed for automatic gear boxes requiring low viscosity ATF.

 ATF LL Life Protect 8 ensures easy shifting under all operating temperatures, without unnecessary friction. Because of the low pour point and the high VI,
 ATF LL Life Protect 8 can be applied in a wide temperature range.

### **SPECIFICATION**

BMW ATF M 1375.4 (8322 0142516) BMW 83 22 2 152 426 BMW 83 22 0 144 137 Chrysler 68157995AA Fiat 9.55550-AV5 Ford MERCON LV & SP GM DEXRON VI Bentley Oil PY112995PA Hyundai Oil 040000C90SG Jaguar Fluid 8432, 02JDE26444 Land Rover TYK 500050, LR023288 Maserati Oil 231603 VW G 055 005 A1/A2/A6 VW G 060 162 A2 M-1375.4/5/6 & M-L 12108 Because of the excellent oxidation and thermal stability, **ATF LL Life Protect 8** keeps its unique properties, so it easily meets the prescribed drain intervals.

A unique combination of synthetic base oils and state-of-the-art additives, guarantee all-round, easy shifting. The low viscosity ensures a fuel economy benefit compared to conventional viscosity ATF's.

MB 236.41 Mazda FZ Honda DW-1 Hyundai / Kia SP-IV/SPH-IV JWS 3324 Mitsubishi SP-IV & ATF J-2 Nissan Matic-S Saab 93 165 147 Toyota WS ZF Lifeguard Fluid 6 (S671 090 255) ZF Lifeguard Fluid 8

## **VALUE ANALYSIS**

		ATF LL 8	ASTM	
Density 20C	Kg/L	0,843	D4052	
Viscosity 100C	cSt	6.0	D445	
Viscosity 40C	cSt	29.4	D445	
Viscosity -40C	cP	<18.000	D2983	
Viscosity Index		154	D2270	
Flash point COC	С	200	D92	
Pour point	С	-46	D6892	
Color		gold		

## AVAILABLE **PACKAGING**

632010 - 1L, 632011 - 5L, 632012 - 20L, 632013 - 60L

The contents of this document is intended to enable the reader to orient themselves on properties and potential applications of BO Motor Oil products. The information in this document at any time and without notice be altered because of continuous product research and development. The analytical data are listed in this product data sheet are typical values. Minor deviations, which may occur during the normal manufacturing process of the product, the quality of the product does not affect. Although this text has been compiled with great care, the compiler accepts no liability for damage caused by incompleteness and / or inaccuracies in the text. The reader is advised to make the final product in consultation with the supplier.



Verkoopvoorwaarden zoals gedeponeerd bij de Kamer Van Koophandel te Eindhoven, onder nr. 4959. Reclamaties binnen 8 dagen na factuurdatum

www.bomotoroil.com